

System UI

GNSYSMG

CHAMELEON GNSYSMG System UI/Management

The system management SW option GNSYMUX enables the system UI for all Chameleons interconnected via a Headend System Group. The System UI gives an overview of interconnected Chameleons in a single web interface via the GN50 embedded switch GT11. Apart from the overview in the System mode, the UI of each individual Chameleon can be reached directly from a drop-down list.

- SYSTEM OVERVIEW WITH SYSTEM STATUS WARNINGS IN A SINGLE VIEW
- OVERVIEW OF ALL CONFIGURED INPUTS IN A SYSTEM OF CHAMELEONS
- OVERVIEW OF ALL CONFIGURED OUTPUTS IN A SYSTEM OF CHAMELEONS
- OVERVIEW OF SERVICES AND SERVICE INFORMATION FOR A SYSTEM OF CHAMELEONS
- SIMPLE ACCESS TO ALL INDIVIDUAL CHAMELEONS IN A SYSTEM VIA DROP-DOWN LIST



Any Video from any Source to any Device

The CHAMELEON product line is the first ever to cover almost every need for Cable-TV and SMATV distribution with only one hardware. The different inputs and outputs are defined by software and hardware options and all software options can be updated any time.



Graphical User Interface for easy set up of complex systems. Simple handling of service remultiplexing and automatic PSI/SI regeneration. Each CHAMELEON contains an embedded web server for management and control. Standard web browsers (Explorer, Mozilla etc.) are supported.

System UI

GNSYSMG

General information about SW options

A SW option purchased for a CHAMELEON can only be used in this specific CHAMELEON. When ordering a SW option for a specific CHAMELEON, the serial number of the CHAMELEON must be stated. SW options can be ordered together with the CHAMELEON HW modules, or separately to an existing CHAMELEON module.

Technical Information

System UI / System Management	
Module types supported	Chameleon modules installed in or connected to a GN50
Number of modules	Typically up to 30 Chameleon modules (UI response time prolonged for systems consisting of large number of Chameleon modules)
Module access	Single IP address access to all modules in a system
System status overview	Overview of all modules with linked warnings for all errors
Settings in system UI	Management and configuration of services via the system UI System Management

SW options	Article number	Description
GNSYSMG	71765	Functionality for system view for (connected) groups of Chameleons

Related SW options, and constraints	
GNMUX	Enabling selection of services from several input sources to an output. Complete and dynamically updated PSI/SI for all digital outputs from a single Chameleon module.
GNSYMUX	Enabling PSI/SI sharing between Chameleons in a system. Complete and dynamically updated PSI/SI for all digital outputs from a system of Chameleon modules.

Note: The system UI functionality is managed by the embedded switch GT11 in GN50. The GNSYSMG is automatically enabled for Chameleons mounted in a GN50. For Chameleons not mounted in a GN50, but connected to a GN50, the GNSYMUX is required for enabling the system UI functionality.

Related Products



CHAMELEON GN40 and GN50

A short description about the product and the benefits with it. For more information, about the GN40 and GN50, please contact xxx or visit our webpage, www.wisi.de.



CHAMELEON GN01

A short description about the product and the benefits with it. For more information, about the GN40 and GN50, please contact xxx or visit our webpage, www.wisi.de.